Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

# Detachable PDU option for compatible SmartOnline UPS Systems, Hardwired Input/C19 Outlets

MODEL NUMBER: **SUPDMB6KIEC**

### Description

The SUPDMB6KIEC UPS backplate with manual transfer switch serves as a replacement for the original backplate provided with SU6000RT4UHVG configurations. Can also be used to convert any high voltage UPS configuration using the SU6000RT4UHVPM power module to support hardwire input and 4 C19 output receptacles. Manual bypass feature ensures maximum availability of connected equipment while UPS maintenance occurs. Can accept input voltages of 200-240 VAC. Hardwire input / 4 C19 output connections.

### Features

### Highlights

- Detachable PDU backplate with manual bypass switch serves as a replacement PDU for configured SU6000RT4UHVG UPS systems
- Can also be used to convert any high voltage UPS configuration using the SU6000RT4UHVPM power module to include C19 outlets
- 4 C19 output receptacles
- Hardwire input supported
- Attaches via unit-specific back panel electrical and bolt-on connections
- Manual bypass feature ensures maximum equipment availability

### System Requirements

- Requires SU6000RT4UHVPM UPS power module in any 200-240V AC configuration

### Package Includes

- SUPDMB6KIEC detachable PDU

## Specifications

| | |
|---|---|
| **General Info** | |
| RoHS | Y |
| **OVERVIEW** | |
| Model Type | PDU Modules |
| Accessories Type | PDU Module |
| **OUTPUT** | |
| Frequency Compatibility | 50 / 60 Hz |
| Output Receptacles | (2) C19 |

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|---|---|
| Output Nominal Voltage | 200, 208, 220, 230, 240 VAC |
| Overload Protection | 2 double pole 20A breakers protect 2 C19 outlets each |
| **INPUT** | |
| Nominal Input Voltage(s) Supported | 200V AC; 208V AC; 230V AC; 240V AC; 220V AC |
| Input Connection Type | Hardwire |
| Voltage Compatibility (VAC) | 200; 208; 220; 230; 240 |
| **PHYSICAL** | |
| Shipping Dimensions (hwd / in.) | 6.9 x 20.1 x 10.8 |
| Shipping Dimensions (hwd / cm) | 17.5 x 51.1 x 27.4 |
| Shipping Weight (lbs.) | 7.7 |
| Shipping Weight (kg) | 3.5 |
| Unit Dimensions (hwd / in.) | 3.3 x 17.2 x 3.2 |
| Unit Dimensions (hwd / cm) | 8.4 x 43.7 x 8.1 |
| Unit Weight (lbs.) | 7.7 |
| Unit Weight (kg) | 3.5 |
| Material of Construction | Sheet metal |
| **CERTIFICATIONS** | |
| Certifications | Tested to UL1778 (USA), CSA (Canada), CE (EU) |
| **WARRANTY** | |
| Product Warranty Period (Worldwide) | 2-year limited warranty |

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.